

Spin light®

Patented Spin Light® Converts Bare Lamp Holder into a Flushmount Fixture



New 9" Brushed Nickel Spin Light® w/ COLOR PREFERENCE®
Model # 56558101
11.5w, 810 Lumens

ETI ADVANTAGE



INSTALLS IN SECONDS

Converts bare lamp holder into attractive LED Flushmount!



SPEEDMOUNT™ DIRECT WIRE ACCESSORY

SPEEDMOUNT® converts your Junction BOX into lamp holder



Perfect for use in closets, as defined in NEC® Section 410.16

Closet Rate!

- ✓ Available in both Traditional and Decorative styles from 5" to 11"
- ✓ COLOR PREFERENCE® models available with selectable 3000K, 4000K, or 5000K!
- ✓ Wall switch controlled, also available in pull chain and motion sensor versions.

AVAILABLE MODELS

Features & Specifications

- Durable impact resistant lens
- 120V
- >80CRI
- TRIAC dimmable
- Temp rating -40°F - 113°F
- L70 >50,000
- 5 Year limited warranty



Traditional Style Spin Light®
Available in 5", 7", & 11"



Traditional Style Spin Light® w/ Motion Sensor
Available in 7"



Traditional Style Spin Light® w/ Pull Chain Control
Available in 7"



7" Brush Nickel Spin Light® w/ COLOR PREFERENCE®

ETI SOLID STATE LIGHTING INC.

North American Headquarters
720 Northgate Parkway
Wheeling, IL 60090

Customer Service
1-855-384-7754
etiorders@ETISSL.com

Visit Us Online
www.ETISSL.com

PART NUMBER GUIDE

CATEGORY	SIZE	LUMENS	CRI/CCT	VOLTAGE	DIMMING	OPTION
SL				SV		

PRODUCT/SKU DETAILS

GENERAL SPECIFICATIONS:

Voltage	120VAC	Frequency	50/60 Hz.	CRI	80
Power Factor	>.90	THD	< 20%	Rating	cULus Damp
Temperature	-4°F to +113°F	Rated Life	50,000 hrs.	Warranty	5 Year Limited

ORDERING GUIDE

Part #	Model #	Description	Replaces	LED Watts	Lumens	LPW	CCT	Product Dim.	CRI	Input Voltage	Case Pack
SLDC-9IN-810LM-8-CP5-SV-N-BN	56558101	9" Decorative COLOR PREFERENCE® Spin Light®, Brushed Nickel	60w	11.5w	810	73	2700K / 3000K / 3500K / 4000K / 5000K	9 x 9 x 4.8 in.	80	120V	2
SL-5-8-840-SV-N	54692142	5" Spin Light®	40w	8.5w	600	71	4000K	5.1 x 5.1 x 2.8 in.	80	120V	5
SL-7-11-830-SV-N	54606211	7" Spin Light®	60w	11.5w	810	70	3000K	7 x 7 x 3.5 in.	80	120V	5
SL-7-83-840-SV-N	54483141	7" Spin Light®	60w	11.5w	830	72	4000K	7 x 7 x 3.9 in.	80	120V	5
SLP-7-83-840-SV-N	54484141	7" Spin Light® - Pull Chain	60w	11.5w	830	72	4000K	7 x 7 x 3.9 in.	80	120V	5
SL-7-81-802-SV-N	54690112	7" COLOR PREFERENCE® Spin Light®	60w	11.5w	810	70	30 / 40 / 5000K	7 x 7 x 3.5 in.	80	120V	5
SL-7-83-840-SV-N-OS	54606342	7" Spin Light® with Motion Sensor	60w	11.5w	830	72	4000K	7 x 7 x 3.5 in.	80	120V	5
SL-11-16-840-SV-N	54652141	11" Spin Light®	100w	22w	1,600	73	4000K	10.9 x 10.9 x 4.2 in.	80	120V	4
SL-11-16-840-SV-N-BN	54652144	11" Spin Light® - Brushed Nickel	100w	22w	1,600	73	4000K	10.9 x 10.9 x 4.2 in.	80	120V	4

PACKAGING SPECIFICATIONS

Part #	Model #	UPC	UCC	Inner Carton Dimensions	Inner Carton Weight	Shipper/Master Carton Dimensions	Shipper/Master Carton Weight
SLDC-9IN-810LM-8-CP5-SV-N-BN	56558101	849489060958	50849489060953	10 x 6 x 10.2 in.	1.7 lbs.	12.6 x 10.6 x 10.9 lbs.	4.3 lbs.
SL-5-8-840-SV-N	54692142	849489001227	50849489001222	7.1 x 3.2 x 5.5 in.	0.9 lbs.	7.6 x 6.2 x 6.2 in.	5.1 lbs.
SL-7-11-830-SV-N	54606211	849489000893	50849489000898	7.4 x 3.9 x 7.6 in.	1 lbs.	20.6 x 8 x 8.3 in.	5.8 lbs.
SL-7-83-840-SV-N	54483141	849489060828	50849489060823	7.4 x 3.9 x 7.6 in.	1.2 lbs.	20.6 x 8 x 8.3 in.	5.8 lbs.
SLP-7-83-840-SV-N	54484141	849489060835	50849489060830	8 x 4.5 x 8.1 in.	1.2 lbs.	20.6 x 8 x 8.3 in.	5.8 lbs.
SL-7-81-802-SV-N	54690112	849489000848	50849489000843	7.5 x 3.9 x 7.6 in.	1 lbs.	20.6 x 8 x 8.3 in.	5.8 lbs.
SL-7-83-840-SV-N-OS	54606342	849489006499	50849489006494	7.5 x 3.9 x 7.6 in.	1.2 lbs.	20.6 x 8 x 8.3 in.	6.5 lbs.
SL-11-16-840-SV-N	54652141	849489000145	50849489000140	12.13 x 4.8 x 12.2 in.	1.9 lbs.	20.4 x 13.2 x 13 in.	10.4 lbs.
SL-11-16-840-SV-N-BN	54652144	849489006550	50849489006555	12.13 x 4.8 x 12.2 in.	1.9 lbs.	20.4 x 13 x 13.4 in.	10.4 lbs.