

Vapor Tight

EZ Install Vapor Tight Fixtures 34w, 51w, & 56w



EZ VAPOR TIGHTS

ETI ADVANTAGE



- ✓ Durable stainless-steel latches
- ✓ Captive hinged lens makes for quick and EZ Installation
- ✓ Suspended or ceiling mount installation, Brackets included!
- ✓ Replaceable light engines and drivers
- ✓ NSF Rated

- ✓ Upgrade options include integrated microwave motion sensor and BBU (Battery Backup Unit)



Microwave Motion Sensor



BBU

AVAILABLE MODELS

Vapor Tight Selection Guide	STANDARD LUMEN 34W 3600 Lm. 4000K	MID LUMEN 51W 5400 LM. 4000K	HIGH LUMEN 56W 7000 LM 4000K*
Base Model	54656241 VT-4-34-840-MV	54465141 VT-4-54-840-MV-D	64501141 VT-4-70-840-MV-D
Base + Microwave Sensor	54656241-I VT-4-34-840-MV-OS	54465141-I VT-4-54-840-MV-D-OS	N/A
Base + BBU	54656341 VT-4-34-840-MV-EM	N/A	N/A
Base + Sensor & BBU	54656341-I VT-4-34-840-MV-EM-OS	N/A	N/A

*Also available in 5000K

Features & Specifications

- Wide 110° beam angle
- 120-227V
- >80CRI
- 0-10V dimmable (51w and 56w)
- Temp rating -4°F - 113°F
- L70 >50,000
- 5 Year limited warranty

ETI SOLID STATE[®]
LIGHTING
INC.

North American Headquarters
720 Northgate Parkway
Wheeling, IL 60090

Customer Service
1-855-384-7754
etiorders@ETISSL.com

Visit Us Online
www.ETISSL.com

PART NUMBER GUIDE



PRODUCT/SKU DETAILS

GENERAL SPECIFICATIONS:

Voltage	120-277VAC	Frequency	50/60 Hz.	CRI	80
Power Factor	>.90	THD	< 20%	Rating	cULus Wet
Temperature	-4°F to +113°F	Rated Life	50,000 hrs.	Warranty	5 Year Limited

ORDERING GUIDE

Part #	Model #	Description	Replaces	LED Watts	Lumens	LPW	CCT
VT-4-34-840-MV	54656241	4' 34w Vapor Tight (NSF)	3 x 32w T8	34w	3,600	106	4000K
VT-4-34-840-MV-OS	54656241-I	4' 34w Vapor Tight with Motion Sensor (NSF)	3 x 32w T8	34w	3,600	106	4000K
VT-4-40-840-MV-EM	54656341	4' 40w Vapor Tight with Battery Back-Up (NSF)	3 x 32w T8	40w	3,600	90	4000K
VT-4-40-840-MV-EM-OS	54656341-I	4' 40w Vapor Tight with Battery Back-Up and Motion Sensor (NSF)	3 x 32w T8	40w	3,600	90	4000K
VT-4-54-840-MV-D	54465141	4' 51w Vapor Tight - 0-10V Dimmable (NSF)	3 x 32w T8	51w	5,400	106	4000K
VT-4-54-840-MV-D-OS	54465141-I	4' 51w Vapor Tight with Motion Sensor - 0-10V Dimmable (NSF)	3 x 32w T8	51w	5,400	106	4000K
VT-4-54-850-MV-D	54465161	4' 51w Vapor Tight - 0-10V Dimmable (NSF)	3 x 32w T8	51w	5,400	106	5000K
VT-4-70-840-MV-D	64501141	4' 56w High Lumen Output Vapor Tight - 0-10V Dimmable	4 x 32w T8	56w	7,000	125	4000K
VT-4-70-850-MV-D	64501161	4' 56w High Lumen Output Vapor Tight - 0-10V Dimmable	4 x 32w T8	56w	7,000	125	5000K

PACKAGING SPECIFICATIONS

Part #	Model #	UPC	UCC	Inner Carton Dimensions	Inner Carton Weight	Shipper/Master Carton Dimensions	Shipper/Master Carton Weight
VT-4-34-840-MV	54656241	849489009599	50849489009594	50 x 4.8 x 3.4 in.	5.1 lbs.	51 x 7.4 x 5.4 in.	11.6 lbs.
VT-4-34-840-MV-OS	54656241-I	849489005089	50849489005084	50 x 4.8 x 3.4 in.	5.5 lbs.	51 x 7.4 x 5.4 in.	11.6 lbs.
VT-4-40-840-MV-EM	54656341	849489009926	50849489009921	50 x 4.8 x 3.4 in.	5.1 lbs.	51 x 7.4 x 5.4 in.	14.9 lbs.
VT-4-40-840-MV-EM-OS	54656341-I	849489001791	50849489001796	50 x 4.8 x 3.4 in.	5.5 lbs.	51 x 7.4 x 5.4 in.	14.9 lbs.
VT-4-54-840-MV-D	54465141	849489009919	50849489009914	50 x 4.8 x 3.4 in.	5.1 lbs.	51.3 x 7.7 x 5.7 in.	12.8 lbs.
VT-4-54-840-MV-D-OS	54465141-I	849489001951	50849489001956	50 x 4.8 x 3.4 in.	5.5 lbs.	51 x 7.4 x 5.4 in.	11.6 lbs.
VT-4-54-850-MV-D	54465161	849489002293	50849489002298	50 x 4.8 x 3.4 in.	5.1 lbs.	51.3 x 7.7 x 5.7 in.	12.8 lbs.
VT-4-70-840-MV-D	64501141	849489002309	50849489002304	47.6 x 5.16 x 3.86 in.	6.5 lbs.	48.3 x 10.9 x 8.3 in.	29.9 lbs.
VT-4-70-850-MV-D	64501161	849489002316	50849489002311	47.6 x 5.16 x 3.86 in.	6.5 lbs.	48.3 x 10.9 x 8.3 in.	29.9 lbs.