



NVLAP LAB CODE 500080-0

Ref. No.: LCZP14040138

Date of Issue: 2014-4-24

Version: 1.0

Total pages: 12



Test report of

IES LM-79-08

Approved Method: Electrical and Photometric

Measurements of Solid-State Lighting Products

Rendered to:

Elec-Tech International Co., Ltd.

NO.1 JINFENG ROAD ,TANGJIAWAN TOWN,XIANGZHOU

DISTRICT,ZHUHAI CITY,GUANGDONG PROVINCE, P.R.China

For products:

Inseparable SSL Luminaire(Residential)

Models:

540743XX("XX" could be 41-50)

(Where "XX" denotes correlated color temperature, 41-50 identifies 4000K)

Test date: 2014-4-24

Test laboratory: LCTECH (Zhongshan) Testing Service Co.,Ltd
2/F.,Technology and Enterprise Development Center, Guangyuan Road,
Xiaolan, Zhongshan, Guangdong, China

Laboratory note:

Complied by:

Thomas Liu

Project Engineer

2014-4-24

Reviewed by:

Richard Li

Technical Manager

2014-4-24

The duplication of this report or parts of it and its use for advertising purposes is only allowed with permission of the testing laboratory. This report contains the result of the examination of the product sample submitted by the applicant. A general statement concerning the quality of the products from the series manufacture cannot be derived therefore. This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Table of Contents


1 General.....	3
1.1 Product Information.....	3
1.2 Reference standards or methods.....	4
1.4 Equipment list.....	4
2 Test conducted and method.....	5
2.1 Ambient Condition.....	5
2.2 Power Supply Characteristics.....	5
2.3 Seasoning and Stabilization.....	5
2.4 Electrical Instrumentation.....	5
2.5 Color Measurement Method.....	5
2.6 Total Luminous Flux Measurement Method.....	5
2.7 Luminous Intensity Distribution Measurement Method.....	5
2.8 Spatial Non-uniformity of Chromaticity.....	5
3 Test Result Summary.....	6
3.1 Electrical data.....	6
3.2 Photometric data.....	6
4 Test Data.....	7
4.1 Spectral Distribution.....	7
4.2 Chromaticity Diagram (CIE 1931).....	7
4.3 ANSI Chromaticity Quadrangles Diagram.....	8
4.4 Color Rendering Details.....	8
4.1 Goniometry Test Data.....	9
4.2 Zonal Lumen Summary.....	9
4.3 Polar Curves.....	10
4.4 Candela Tabulation.....	11
Attachment 1	12

1 General


1.1 Product Information

Brand Name	ETI,CE
Trade Mark	-
Lamp Type	Inseparable SSL Luminaire(Residential)
Model Number	540743XX("XX" could be 41-50)
Rated Inputs	120V 60Hz
Rated Power	14W
Rated Initial Lamp Lumens	1000lm
Declared CCT	4000K
Power Supply	SX-AD01400121-0250
LED Package, Array or Module	62-217D manufactured by Everlight Electronics.,Ltd
Date of Receipt Samples	2014-4-19
Quantity of Receipt Samples	1 units

Photo



Over view



Part view



1.2 Reference standards or methods

The following standards are partly or totally used or referenced for test:

No.	Name
ANSI/NEMA/ ANSLG C78.377-2011 [#]	Specifications for the Chromaticity of Solid State Lighting Products
ANSI C82.77-2002	Harmonic Emission Limits—Related Power Quality Requirements for Lighting Equipment
CIE Pub. No. 13.3-1995	Method of Measuring and Specifying Color Rendering of Light Sources
CIE Pub. No. 15:2004	Colorimetry
IES LM-79-08	Electrical and Photometric Measurements of Solid-State Lighting Products

[#] For reference only.

1.4 Equipment list

ID	Instrument	Model name	Cal. date	Next cal. Date
AC Power supply	LC-I-923	CHP-500	2014-03-04	2015-03-03
AC Power supply	LC-I-953	APW-110N	2014-03-04	2015-03-03
Power analyzer	LC-I-928	WT210	2014-03-21	2015-03-20
Power analyzer	LC-I-954	WT210	2014-03-04	2015-03-03
Multimeter	LC-I-972	Fluke 17B	2013-08-14	2014-08-13
Photometric colorimetric electric system (2 meter sphere)	LC-I-900	SPR3000	Before use	Before use
Standard lamp	LC-I-961	24V/100W	2013-10-22	2014-10-21
Goniophotometer(with mirror)	LC-I-902	GMS2000	2013-05-13	2014-05-12
Wireless temperature transmitter	LC-I-958	DWRP-B(0)	2013-08-22	2014-08-21
Wireless temperature transmitter	LC-I-959	DWRP-B(0)	2013-08-22	2014-08-21

2 Test conducted and method

2.1 Ambient Condition

The ambient temperature in which measurements are being taken was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, the air flow around the sample(s) being tested did not affect the performance.

2.2 Power Supply Characteristics

The AC power supply had a sinusoidal voltage wave shape at the prescribed frequency (60 Hz) such that the RMS summation of the harmonic components does not exceed 3 percent of the fundamental during operation of the test item.

The voltage of AC power supply (RMS voltage) applied to the device under test was regulated to within ± 0.2 percent under load.

2.3 Seasoning and Stabilization

No seasoning was performed in accordance with IESNA LM-79-08. And before the measurement, the sample was stabilized until the light output and power variations were less than 0.5% in 30 minutes intervals (3 readings, 15 minutes apart).

2.4 Electrical Instrumentation

The calibration uncertainties of the instruments for AC voltage and current were less than 0.2 percent, and the calibration uncertainty of the AC power meter was less than 0.5 percent (95 % confidence interval, $k=2$).

2.5 Color Measurement Method

Spectral radiant flux was measured by a sphere (2 meter)-spectroradiometer system, and the color characteristics (Color rendering index, correlated color temperature, chromaticity coordinate) were calculated from these by software automatically.

2.6 Total Luminous Flux Measurement Method

Total luminous flux was measured by both sphere-spectroradiometer system and goniophotometer. Spectral radiant flux was measured by a sphere (2 meter)-spectroradiometer system (bandwidth: 1nm), and the total luminous flux was calculated from these by software automatically. Light intensity distribution was measured by a type C goniophotometer (with mirror) which can keep the sample in burn position when the tests conduct, and the total luminous flux was calculated from the intensity data by software automatically.

2.7 Luminous Intensity Distribution Measurement Method

Luminous intensity distribution was measured by a mirror-type goniophotometer (Type C) which can keep the sample in burn position when the tests conduct, and the kinds of graph were generated by software automatically.

2.8 Spatial Non-uniformity of Chromaticity

The customer did not require this measurement.

3 Test Result Summary

3.1 Electrical data

Criteria Item	Result (Sphere)	Result (Goniophotometer)
Input Voltage	120.07V-60Hz	119.99V-60Hz
Input Current	0.113 A	0.112 A
Total Power	13.50 W	13.39 W
Power Factor	0.996	0.993
I-THD	4.02%	-
Off-state Power	0.0 W	-


3.2 Photometric data

Criteria Item	Result (Sphere)	Result (Goniophotometer)
Total Lumens	1089.53 lm	1068.66 lm
Luminaire Efficacy	80.71 lm/W	79.81 lm/W
Correlated Color Temperature (CCT)	4183 K	-
Color Rendering Index (CRI)	89.9	-
R9	54	-
Chromaticity Coordinate (x,y)	x=0.3712, y=0.3651	-
Chromaticity Coordinate (u,v)	u=0.2237, v=0.3300	-
Chromaticity Coordinate (u',v')	u'=0.2237, v'=0.4950	-
Duv	-0.0027	-
Beam Angle(50% I _{max})	-	122°


Note: N.A.

4 Test Data

4.1 Spectral Distribution




4.2 Chromaticity Diagram (CIE 1931)





4.3 ANSI Chromaticity Quadrangles Diagram



4.4 Color Rendering Details

R1	R2	R3	R4	R5
90	94	95	88	89
R6	R7	R8	R9	R10
89	92	82	54	84
R11	R12	R13	R14	R15
87	68	91	97	88

4.1 Goniometry Test Data

CIE Type	Semi-Direct	Basic Luminous Shape	Circular w/ Sides
Spacing Criteria (0-180)	1.32	Luminous Length	0.29 m
Spacing Criteria (90-270)	1.32	Luminous Width	0.29m
Spacing Criteria (Diagonal)	1.44	Luminous Height	0.08m
Test Distance	18.54		

4.2 Zonal Lumen Summary

Zone	Lumens	%Lamp	%Fixt
0-30	209.93	19.6	19.6
0-40	348.38	32.6	32.6
0-60	635.87	59.5	59.5
0-90	891.56	83.4	83.4
90-120	92.47	8.7	8.7
90-130	116.2	10.9	10.9
90-150	154.87	14.5	14.5
90-180	177.09	16.6	16.6
0-180	1068.66	100	100

Total Luminaire Efficiency = 100%

ZONAL LUMEN SUMMARY


Zone	Lumens
0-10	25.09
10-20	72.68
20-30	112.17
30-40	138.45
40-50	147.97
50-60	139.51
60-70	115.86
70-80	84.33
80-90	55.51
90-100	37.31
100-110	29.34
110-120	25.82
120-130	23.73
130-140	21.2
140-150	17.47
150-160	12.62
160-170	7.41
170-180	2.19



LCTECH



4.3 Polar Curves



Maximum Candela = 264.9 Located At Horizontal Angle = 0, Vertical Angle = 5
1 - Vertical Plane Through Horizontal Angles (0 - 180)
2 - Vertical Plane Through Horizontal Angles (90 - 270)

4.4 Candela Tabulation

	<u>0</u>	<u>15</u>	<u>30</u>	<u>45</u>	<u>60</u>	<u>75</u>	<u>90</u>
0	264.11	264.11	264.11	264.11	264.11	264.11	264.11
5	264.90	263.80	263.62	263.54	263.38	263.35	263.32
10	262.66	261.57	261.37	261.29	261.18	261.05	261.15
15	258.47	257.38	257.24	257.15	257.05	257.03	256.92
20	252.40	251.39	251.26	251.13	251.07	251.07	251.13
25	244.38	243.36	243.21	243.10	242.94	243.07	243.07
30	234.36	233.44	233.24	233.09	233.12	232.98	233.12
35	222.38	221.32	221.22	221.05	220.99	221.06	221.24
40	208.49	207.49	207.32	207.30	207.16	207.37	207.24
45	192.66	192.00	191.78	191.62	191.73	191.74	191.99
50	175.11	174.68	174.62	174.33	174.31	174.44	174.65
55	156.81	156.02	155.99	155.99	156.00	155.99	155.92
60	137.03	136.65	136.34	136.47	136.47	136.49	136.46
65	117.30	116.70	116.87	116.74	116.80	116.67	116.90
70	97.93	97.41	97.25	97.45	97.51	97.66	97.64
75	79.32	79.17	79.32	79.27	79.18	79.20	79.21
80	63.26	63.15	63.07	63.38	63.45	63.37	63.26
85	50.06	49.93	49.92	50.07	50.15	50.19	50.34
90	40.08	40.05	40.14	40.19	40.14	40.23	40.30
95	33.50	33.45	33.46	33.56	33.53	33.63	33.60
100	29.51	29.45	29.48	29.50	29.60	29.56	29.58
105	27.57	27.41	27.43	27.46	27.47	27.48	27.53
110	26.50	26.42	26.40	26.42	26.45	26.49	26.48
115	25.90	25.81	25.77	25.82	25.82	25.83	25.90
120	26.00	25.93	25.91	25.89	25.91	25.97	26.00
125	26.57	26.43	26.41	26.44	26.44	26.49	26.48
130	27.10	27.02	26.98	26.95	27.00	27.00	27.03
135	27.53	27.38	27.34	27.37	27.39	27.45	27.45
140	27.79	27.64	27.62	27.64	27.73	27.78	27.79
145	27.93	27.82	27.76	27.82	27.88	27.92	27.95
150	27.79	27.77	27.81	27.82	27.87	27.95	28.00
155	27.29	27.15	27.16	27.27	27.33	27.28	27.27
160	26.62	26.49	26.55	26.60	26.63	26.69	26.74
165	26.88	26.71	26.66	26.61	26.66	26.53	26.64
170	24.51	24.39	24.47	24.33	24.32	24.14	24.27
175	21.88	21.54	21.35	21.35	21.31	21.21	21.11
180	24.92	24.92	24.92	24.92	24.92	24.92	24.92



LCTECH



Attachment 1

U.S. Department of Energy

Lighting Facts^{CM} Uniform LM-79 Reporting Template

Laboratory Information

Name of test lab	LCTECH (Zhongshan) Testing Service Co.,Ltd
Date of test report	2014-4-24
Test report number	LCZP14040138
Laboratory contact name	Richard Li

Product Information

Manufacturer	Elec-Tech International Co., Ltd	
Brand name	ETI,CE	
Model number	540743XX("XX" could be 41-50)	
SKU (if available)	N/A	
Type of luminaire (for integral lamps, list base type and lamp type)	Inseparable SSL Luminaire(Residential)	
Luminaire aperture	N/A	in.
Luminaire height	0.08	in.
Luminaire length	0.29	in.
Luminaire width	0.29	in.
Number of units (modular products)	N/A	

Electrical Measurements	Integrating sphere output	Goniophotometer Output	
Input wattage	13.50	13.38	W
Input current	0.113	0.112	A
Input voltage (AC)	120.07	119.99	V
Power factor	0.996	0.993	
Off-state power	0.0	-	W

Photometric Characteristics

Total initial lumen output	1089.531	1068.66	lm
Initial luminaire efficacy	80.706	79.81	lm/W
Correlated color temperature / CCT	4183	K	
Color rendering index / CRI	89.9		
Rg value	54		
Duv	-0.0027		

Luminous Intensity Distribution		Goniophotometer Output	
Center beam candlepower (if applicable)		265.498	cd
Beam angle (if applicable)		120.0	°
Zonal lumens in the 0°-60° zone	--	65.264	%
Zonal lumens in the 60°-90° zone		18.164	%
Zonal lumens in the 90°-120° zone		8.653	%
Zonal lumens in the 120°-180° zone		7.919	%

****End of test report****