



4' High Lumen Output Vapor Tight with Motion Sensor

5400 lm | 120-277VAC | Ordering 54465141-I | Part VT-4-51-840-MV-OS

- > Energy Saving 51 Watt Integrated LED
- > Cool White 4000K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free - No Bulb Replacements
- > 5 Year Limited Warranty



SPECIFICATIONS

Model	54465141-I
Part	VT-4-51-840-MV-OS
Certification	54465141-I
Description	4' High Lumen Output Vapor Tight with Motion Sensor
Input Voltage (VAC)	120-277
Wattage	51
Dimmability	0-10V Dimmable
Average Rated Life ¹	50,000 hours
Typical Lumens ²	5400
CCT ³	4000K
Location Rating	UL Wet (IP65 Rated)
CRI ⁴	≥80
Beam Angle Operating	120°
Temperature	Min -4°F (-20° C) Max 113°F (45° C)
Power Factor	>0.9
R9	20
DUV	-0.00149
CBCP	1500
Operating Frequency (Hz)	50/60

- 1 Hours lifetime with 70% lumen maintenance
- 2 Thermally stable typical lumens (±10%)
- 3 Thermally stable CCT (±10%)
- 4 Color rendering index/Ra

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754



LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens)	5400
Watts	51
Lumens per Watt (Efficacy)	105.88

Color Accuracy Color Rendering Index (CRI)	80
---	----

Light Color
Correlated Color Temperature (CCT) 4000 (Bright White)

2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: 5BAM-HC53F1 (11/2/2017)
Model Number: 544651##(##=41-50)
Type: Luminaire - Linear



4' High Lumen Output Vapor Tight with Motion Sensor

5400 lm | 120-277VAC | Ordering 54465141-I | Part VT-4-51-840-MV-OS



SHIPPING INFORMATION

Ordering	54465141-I
Part	VT-4-51-840-MV-OS
UPC	849489009919
Product Dimensions (L x W x H in.)	48 x 4 1/2 x 3
Product Dimensions (L x W x H cm.)	122 x 12 x 8
Product Weight (lbs.)	4.12
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	2
Master Carton Bar Code	50849489009914
Master Carton Dimensions (L x W x H in.)	51 x 7 x 5
Master Carton Dimensions (L x W x H cm.)	129 x 19 x 14
Master Carton Weight (lbs)	11.57
Pallet Quantity	110

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256