



Angled LEDs deliver more light to sidewalk and street surfaces.

ETI ADVANTAGE



- ✓ Replaces HID Lamps from 150w to 250w
- ✓ Up to 150 LPW efficacy
- ✓ IP64 moisture rating
- ✓ Intelligent thermal protection for superior enclosed fixture performance

- ✓ Integrated 6kV surge protection
- ✓ DLC APPROVED (EX39 ONLY)
- ✓ 5 Year Warranty , L70 >50,000 HRS



Upgrade to LED but Keep Existing, Historically Significant Light Fixtures!

Angled Led Array

- Delivers brighter lighting to walkways, grassy areas and roads when used in decorative post tops
- Convertible for “base-up” or “base-down” installations

Superior Optical Performance & Electronic Design

- Intelligent thermal protection for superior enclosed fixture performance

Robust, Durable Construction

- IP64 rated housing superior when installed in leaky fixtures.
- EX39 base version

HID Replacement Lamps

Directional Post Top Retrofit



PT-30-XXX-MV

30W LED | Repl. 150W | 3/4/5000K | EX39 Base



PT-50-XXX-MV

50W LED | Repl. 175W | 3/4/5000K | EX39 Base



PT-80-850-MV

80W LED | Repl. 250W | 3/4/5000K | EX39 Base

PART NUMBER GUIDE

CATEGORY

PT

WATTS

CRI/CCT

VOLTAGE

MV

PRODUCT/SKU DETAILS

GENERAL SPECIFICATIONS:

Voltage	120-277VAC	Frequency	50/60 Hz.	CRI	80
Power Factor	>.90	THD	< 20%	Rating	cULus Wet
Temperature	-40°F to +118°F	Rated Life	50,000 hrs.	Warranty	5 Year Limited

ORDERING GUIDE

Part #	Model #	Description	Replaces	LED Watts	Lumens	LPW	CCT	Product Dim.	CRI	Input Voltage	Case Pack
PT-30-830-MV	62707111*	30W HID Post Top Repl. Lamp, 3000K, EX39	100w HID	30w	3,900	130	3000K	5.1 x 5.1 x 7 in.	80	120-277V	6
PT-30-840-MV	62707141*	30W HID Post Top Repl. Lamp, 4000K, EX39	100w HID	30w	3,900	130	4000K	5.1 x 5.1 x 7 in.	80	120-277V	6
PT-30-850-MV	62707161	30W HID Post Top Repl. Lamp, 3000K, EX39	100w HID	30w	3,900	130	5000K	5.1 x 5.1 x 7 in.	80	120-277V	6
PT-50-830-MV	62707211*	50W HID Post Top Repl. Lamp, 3000K, EX39	175w HID	50w	6,500	130	3000K	5.1 x 5.1 x 7 in.	80	120-277V	6
PT-50-840-MV	62707241*	50W HID Post Top Repl. Lamp, 4000K, EX39	175w HID	50w	6,500	130	4000K	5.1 x 5.1 x 7 in.	80	120-277V	6
PT-50-850-MV	62707261	50W HID Post Top Repl. Lamp, 4000K, EX39	175w HID	50w	6,500	130	5000K	5.1 x 5.1 x 7 in.	80	120-277V	6
PT-80-830-MV	62708111*	80W HID Post Top Repl. Lamp, 3000K, EX39	250w HID	80w	10,400	130	3000K	5.1 x 5.1 x 7.9 in.	80	120-277V	6
PT-80-840-MV	62708141*	80W HID Post Top Repl. Lamp, 4000K, EX39	250w HID	80w	10,400	130	4000K	5.1 x 5.1 x 7.9 in.	80	120-277V	6
PT-80-850-MV	62708161	80W HID Post Top Repl. Lamp, 5000K, EX39	250w HID	80w	10,400	130	5000K	5.1 x 5.1 x 7.9 in.	80	120-277V	6

PACKAGING SPECIFICATIONS

Part #	Model #	UPC	UCC	Product Carton Dimensions	Product Carton Weight	Shipper/Master Carton Dimensions	Shipper/Master Carton Weight
PT-30-830-MV	62707111*	849489007267	50849489007262	9.5 x 7.1 x 7.1 in.	1.7 lbs.	22.4 x 10.4 x 15.5 in.	12.4 lbs.
PT-30-840-MV	62707141*	849489007274	50849489007279	9.5 x 7.1 x 7.1 in.	1.7 lbs.	22.4 x 10.4 x 15.5 in.	12.4 lbs.
PT-30-850-MV	62707161	849489007281	50849489007286	9.5 x 7.1 x 7.1 in.	1.7 lbs.	22.4 x 10.4 x 15.5 in.	12.4 lbs.
PT-50-830-MV	62707211*	849489007298	50849489007293	9.5 x 7.1 x 7.1 in.	1.9 lbs.	22.4 x 10.4 x 15.5 in.	13.5 lbs.
PT-50-840-MV	62707241*	849489007304	50849489007309	9.5 x 7.1 x 7.1 in.	1.9 lbs.	22.4 x 10.4 x 15.5 in.	13.5 lbs.
PT-50-850-MV	62707261	849489007311	50849489007316	9.5 x 7.1 x 7.1 in.	1.9 lbs.	22.4 x 10.4 x 15.5 in.	13.5 lbs.
PT-80-830-MV	62708111*	849489007328	50849489007323	10.4 x 7.1 x 7.1 in.	2.1 lbs.	22.4 x 10.4 x 15.5 in.	15.4 lbs.
PT-80-840-MV	62708141*	849489007335	50849489007330	10.4 x 7.1 x 7.1 in.	2.1 lbs.	22.4 x 10.4 x 15.5 in.	15.4 lbs.
PT-80-850-MV	62708161	849489007342	50849489007347	10.4 x 7.1 x 7.1 in.	2.1 lbs.	22.4 x 10.4 x 15.5 in.	15.4 lbs.