


LowPro

# 3", 4" & 5/6" COLOR PREFERENCE® Downlights Low Profile Design



Available in 3", 4", and 5/6" sizes

**ETi** ADVANTAGE



- ✓ Unmatched slim 1.3" profile
- ✓ IC insulation rating
- ✓ UL wet rating
- ✓ Meets NECA 410.16 requirement
- ✓ Mounting guide plate available for each size



**COLOR PREFERENCE®**

- ✓ 12'/20" power cable extenders available
- ✓ TRIAC dimmable

## Tight Ceiling Clearance? No Problem!

ETi's LowPro downlights are designed for difficult low clearance installations TRIAC dimmable and suitable for wet environments

### Design

- 1.3" profile great for tight of enclosures

### Technology

- 4 CCT COLOR PREFERENCE® technology delivers total choice of CCT: 2700K, 3000K, 4000K, or 5000K

### Control

- Dimmable with TRIAC dimmer

### Features & Specifications

- 120V
- 90CRI
- UL Wet Rating
- Temp rating -4°F - 104 °F
- 12" and 20" cord extenders available

\*USA Patent 15/871,433

# LowPro

## 3", 4" & 5/6" COLOR PREFERENCE® Downlights Low Profile Design



Integrated trim ring

22" connect cord  
Included. 12" and  
20" cord extenders  
available

✓ 3" COLOR PREFERENCE® - 53809111  
DL-3-47-906-SV-D

✓ 4" COLOR PREFERENCE® - 53808211  
DL-4-65-906-SV-D

✓ 5/6" COLOR PREFERENCE® - 53807211  
DL-5-90-906-SV-D

Note: 5/6" model include a "goof ring" to fit  
6" openings

### PART NUMBER GUIDE

CATEGORY	SIZE	WATTS	CRI/CCT	VOLTAGE	DIMMABILITY
DL			906	SV	D

### PRODUCT/SKU DETAILS

#### GENERAL SPECIFICATIONS:

<b>Voltage</b>	120VAC	<b>Frequency</b>	50/60 Hz.	<b>CRI</b>	90
<b>Power Factor</b>	>.90	<b>THD</b>	< 20%	<b>Rating</b>	cULus Wet
<b>Temperature</b>	-4°F to +113°F	<b>Rated Life</b>	50,000 hrs.	<b>Warranty</b>	5 Year Limited

### ORDERING GUIDE

Part #	Model #	Description	LED				CCT	Product Dim.	CRI	Input Voltage	Case Pack
			Replaces	Watts	Lumens	LPW					
DL-3-47-906-SV-D	53809111	3" LowPro Recessed Downlight with COLOR PREFERENCE® - TRIAC Dimming	45w Par	8.5w	470	55	27/30/40/5000K	3.14 x 1.3 in.	90	120V	24
DL-4-65-906-SV-D	53808211	4" LowPro Recessed Downlight with COLOR PREFERENCE® - TRIAC Dimming	65w Par	11w	650	59	27/30/40/5000K	4.88 x 1.3 in.	90	120V	20
DL-5-90-906-SV-D	53807211	5"/6" LowPro Recessed Downlight with COLOR PREFERENCE® - TRIAC Dimming	65w Par	15w	900	60	27/30/40/5000K	5.9 x 1.3 in.	90	120V	20
	90600729	6in Downlight Trim Kit for 5" LowPro	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	50
LPGP-3in	70306101	Guide plate for LowPro downlight 3in	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	24
LPGP-4in	70307101	Guide plate for LowPro downlight 4in	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20
LPGP-5in	70308101	Guide plate for LowPro downlight 5in	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20
NA	90600713	12' extension cord for edgelit down lights single pack	N/A	N/A	N/A	N/A	N/A	12.0 x 1 in.	N/A	N/A	10
NA	90600714	20' extension cord for edgelit down lights single pack	N/A	N/A	N/A	N/A	N/A	20.0 x 1 in.	N/A	N/A	10

## PACKAGING SPECIFICATIONS

Part #	Model #	UPC	UCC	Inner Carton Dimensions	Inner Carton Weight	Shipper/Master Carton Dimensions	Shipper/Master Carton Weight
DL-3-47-906-SV-D	53809111	849489003931	50849489003936	5.0 x 4.0 x 5.0 in.	0.8 lbs.	17.1 x 15.6 x 10.8 in.	24.9 lbs.
DL-4-65-906-SV-D	53808211	849489003948	50849489003943	5.7 x 4.3 x 5.6 in.	1.0 lbs.	22.8 x 12.1 x 12.3 in.	24.9 lbs.
DL-5-90-906-SV-D	53807211	849489003955	50849489003950	7.2 x 3.9 x 7.2 in.	1.2 lbs.	20.7 x 15.1 x 15.2 in.	31.3 lbs.
	90600729	849489063126	50849489063121	7 x .1 in.	0.17	8.43 x 7.24 x 7.95 in.	8.8 lbs.
LPGP-3in	70306101	849489063164	50849489063164	N/A	N/A	26.57 x 6.69 x 1.97 in.	
LPGP-4in	70307101	849489063171	50849489063176	N/A	N/A	26.57 x 7.09 x 1.97 in.	
LPGP-5in	70308101	849489063188	50849489063183	N/A	N/A	26.57 x 7.68 x 1.97 in.	
NA	90600713	849489060941	50849489060946	N/A	N/A	9.06 x 5.91 x 5.12 in.	2.5 lbs.
NA	90600714	849489060934	50849489060939	N/A	N/A	10.63 x 5.91 x 5.12 in.	3.5 lbs.

## COMPATIBLE DIMMERS

**LUTRON: DVCL-153, CTCL-153P, TGCL-153P, MACL-153M, PD-6WCL, LECL-153, SCL-153P, NTCL-250, GT-150**

**LEVITON: 6674, 6672, IPL06-10Z, DSL06-1LZ, TSL06, RDL06**

**EATON: SAL06P2**

**COOPER: DLC03P, SUT7, TAL06P2**