



4' Vapor Tight Built-in Battery Backup and Motion Sensor

3600 lms | 120-277VAC | Model 54656341-I | Part VT-4-40-840-MV-EM-OS

- > Energy Saving 40 Watt Integrated LED
- > Cool White 4000k CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



SPECIFICATIONS

Model	54656341-I
Part	VT-4-40-840-MV-EM-OS
Description	4' Vapor Tight Built-in Battery Backup and Motion Sensor
Input Voltage (VAC)	120-277
Wattage	40
Dimmability	Non-dimmable
Average Rated Life ¹	50,000 hours
Typical Lumens ²	3600
CCT ³	4000k
Location Rating	UL Wet
CRI ⁴	≥80
Beam Angle	NA
Operating Temperature	Min -22°F (-30° C), Max 113°F (45° C)
Power Factor	>0.9
R9	16
DUV	0.0011
CBCP	1043
Operating Frequency (Hz)	50/60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





4' Vapor Tight Built-in Battery Backup and Motion Sensor

3600 lms | 120-277VAC | Model 54656341-I | Part VT-4-40-840-MV-EM-OS

SHIPPING INFORMATION

Model	54656341-I
Part	VT-4-40-840-MV-EM-OS
UPC	849489001791
Product Dimensions (L x W x H in.)	48 x 4.6 x 3
Product Dimensions (L x W x H cm.)	122 x 11.7 x 7.6
Product Weight (lbs.)	7.05
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	2
Master Carton Bar Code	50849489001796
Master Carton Dimensions (L x W x H in.)	50.91 x 7.32 x 5.35
Master Carton Dimensions (L x W x H cm.)	129.3 x 18.6 x 13.6
Master Carton Weight (lbs)	15.40
Pallet Quantity	110

COMPATIBILITY

Dimmers: NA
Sensors: 90600145

AVAILABLE ACCESSORIES

Model	Part	Description	Wattage	Input Voltage	Case Pack
90600145	NA	ON/OFF motion sensor	NA	120-277	4

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Northgate Parkway
Wheeling, IL 60090
Phone: 855.384.7754
Fax: 847.383.6256

SpecSheet# 54656341-I | 2019.07.15CN