



## 4' T8 Ballast Bypass Shatter Resistant Glass Tube - Power Either End

1800 lms | 120-277VAC | Model 64101163 | Part T8BP-4-12-850-MV-DE-PET

- > Base G13 Bi-Pin
- > Power Either End
- > Daylight 5000k CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty




### SPECIFICATIONS

<b>Model</b>	64101163
<b>Part</b>	T8BP-4-12-850-MV-DE-PET
<b>Description</b>	4' T8 Ballast Bypass Shatter Resistant Glass Tube - Power Either End
<b>Input Voltage (VAC)</b>	120-277
<b>Wattage</b>	12
<b>Dimmability</b>	Non-Dim
<b>Average Rated Life<sup>1</sup></b>	50,000 hours
<b>Typical Lumens<sup>2</sup></b>	1800
<b>CCT<sup>3</sup></b>	5000k
<b>Location Rating</b>	UL Damp
<b>CRI<sup>4</sup></b>	80
<b>Beam Angle</b>	NA
<b>Operating Temperature</b>	Min -4°F (-20° C), Max 113°F (45° C)
<b>Power Factor</b>	>0.9
<b>R9</b>	7
<b>DUV</b>	0.0015
<b>CBCP</b>	NA
<b>Operating Frequency (Hz)</b>	50/60


1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

#### Below is the line drawing for wiring:

1 Tube with Instant Start Ballast Removed



1 Tube with Program Start or Rapid Start Ballast Removed:



**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754





## 4' T8 Ballast Bypass Shatter Resistant Glass Tube - Power Either End

1800 lms | 120-277VAC | Model 64101163 | Part T8BP-4-12-850-MV-DE-PET

### SHIPPING INFORMATION

<b>Model</b>	64101163
<b>Part</b>	T8BP-4-12-850-MV-DE-PET
<b>UPC</b>	849489060996
<b>Product Dimensions (L x W x H in.)</b>	47.6 x 1.02 x 1.02
<b>Product Dimensions (L x W x H cm.)</b>	121 x 2.6 x 2.6
<b>Product Weight (lbs.)</b>	0.2
<b>Inner Carton Quantity</b>	N/A
<b>Inner Carton Bar Code</b>	N/A
<b>Inner Carton Dimensions (L x W x H in.)</b>	N/A
<b>Inner Carton Dimensions (L x W x H cm.)</b>	N/A
<b>Inner Carton Weight (lbs)</b>	N/A
<b>Master Carton Quantity</b>	25
<b>Master Carton Bar Code</b>	50849489060991
<b>Master Carton Dimensions (L x W x H in.)</b>	48.8 x 5.9 x 5.9
<b>Master Carton Dimensions (L x W x H cm.)</b>	124 x 15 x 15
<b>Master Carton Weight (lbs)</b>	12.98
<b>Pallet Quantity</b>	2400

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.ETiSSL.com/fcc15b](http://www.ETiSSL.com/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Wheeling, IL 60090  
Phone: 855.384.7754  
Fax: 847.383.6256