

# 2FT Linear High Bay

18,000 lms | 120-277VAC | Model 50232162 | Part HB-160-850-MV-D

- > Energy Saving 160 Watt Integrated LED
- > Daylight 5000k CCT
- > Rated Life: 50,000 Hours
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

<b>Model</b>	50232162
<b>Part</b>	HB-160-850-MV-D
<b>Certification</b>	50232162-B
<b>Description</b>	2FT Linear High Bay, 0-10V Dimmable
<b>Input Voltage (VAC)</b>	120-277
<b>Wattage</b>	160
<b>Dimmability</b>	0-10V Dimmable
<b>Average Rated Life<sup>1</sup></b>	50,000 hours
<b>Typical Lumens<sup>2</sup></b>	18,000
<b>CCT<sup>3</sup></b>	5000k
<b>Location Rating</b>	UL Damp
<b>CRI<sup>4</sup></b>	80
<b>Beam Angle</b>	80°
<b>Operating Temperature</b>	Min -40°F (-40° C), Max 113°F (45° C)
<b>Power Factor</b>	>0.9
<b>R9</b>	NA
<b>DUV</b>	NA
<b>CBCP</b>	NA
<b>Operating Frequency (Hz)</b>	50/60

<sup>1</sup> Hours lifetime with 70% lumen maintenance

<sup>2</sup> Thermally stable typical lumens (±10%)

<sup>3</sup> Thermally stable CCT (±10%)

<sup>4</sup> Color rendering index/Ra

### TO ORDER:

[www.ETiSSL.com](http://www.ETiSSL.com)

Call: 1.855.ETi.SSLI

1.855.384.7754





# 2FT Linear High Bay

18,000 lms | 120-277VAC | Model 50232162 | Part HB-160-850-MV-D

## SHIPPING INFORMATION

Model	50232162
Part	HB-160-850-MV-D
Certification	50232162-B
UPC	849489009988
Product Dimensions (L x W x H in.)	24.72 x 12.60 x 3.62
Product Dimensions (L x W x H cm.)	62.8 x 32.0 x 9.2
Product Weight (lbs.)	12.13
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	1
Master Carton Bar Code	50849489009983
Master Carton Dimensions (L x W x H in.)	26.97 x 14.45 x 5.35
Master Carton Dimensions (L x W x H cm.)	68.5 x 36.7 x 13.6
Master Carton Weight (lbs)	14.3
Pallet Quantity	40

## COMPATIBILITY

Dimmer Brand	Dimmer Model#
Lutron	DVTV-IV
Lutron	DVSTV-WH
Lutron	NFTV-WH
Lutron	NTSTV-DV-WH
Lutron	DVTV-WH
Leviton	IP710-DLZ

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.ETiSSL.com/fcc15b](http://www.ETiSSL.com/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

ETi Solid State Lighting, Inc.  
720 Northgate Parkway  
Wheeling, IL 60090  
Phone: 855.384.7754  
Fax: 847.383.6256