

4" Color Preference Downlight with Nighlight Trim

625 lm | 120VAC | Model 53805102 | Part DL-4-625-907-SV-D

- > Triac Dimming
- > Energy Saving 10.5 Watt Integrated LED
- > Uses 83% less energy than equivalent 60 watt incandescent bulb
- > Color Selectable
 - 2700K Warm White
 - 3000K Soft White
 - 3500K Bright White
 - 4000K Cool White
 - 5000K Day light
 - 2000K Nighlight Trim
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > IC Rated for Direct Contact with Insulation



SPECIFICATIONS

Model	53805102
Part	DL-4-625-907-SV-D
Certification	53805102
Description	4" Color Preference Downlight with Nighlight Trim
Input Voltage (VAC)	120V
Wattage	10.5W
Dimmability	Triac Dimming
Average Rated Life ¹	50,000 hours
Typical Lumens ²	625lm
CCT ³	2700/3000/3500/4000/5000K
Location Rating	UL Wet Location
CRI ⁴	90
Beam Angle Operating	100
Temperature	Min -4°F (-20° C), Max 104°F (40° C)
Power Factor	>0.9
R9	57
DUV	0.0015
CBCP	N/A
Operating Frequency (Hz)	60Hz

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





4" Color Preference Downlight with Highlight Trim

625 lm | 120VAC | Model 53805102 | Part DL-4-625-907-SV-D

SHIPPING INFORMATION

Model	53805102
Part	DL-4-625-907-SV-D
UPC	849489004020
Product Dimensions (L x W x H in.)	4 ⁷ / ₈ X 3
Product Dimensions (L x W x H cm.)	12 ¹ / ₂ X 7 ¹ / ₂
Product Weight (lbs.)	0.59
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	8
Master Carton Bar Code	50849489004025
Master Carton Dimensions (L x W x H in.)	14 X 12 X 6
Master Carton Dimensions (L x W x H cm.)	36 X 31 X 16
Master Carton Weight (lbs)	6.96
Pallet Quantity	N/A

COMPATIBILITY

Dimmers:

Lutron: DVCL-153PR-WH, CTCL-153PDH-WH, TGCL-153PH-WH, MACL-153MH-WH, P-PKG1W-WH-R

Leviton: R62-06674-P0W, R12-06672-1LW, R50-IPL06-10M

Eaton: AAL06-C1, SAL06P-W-K

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256