

Emergency Light W/Remote Capability (2-head)

249lms | 120/277VAC | Model 55501201 | Part EM-EL-RC

- > Remote capability
- > 120/277VAC Dual voltage operation
- > Test switch and charge indicator
- > Maximum 24 hours for full recharge time
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Minimum 90 minutes emergency operation
- > 2 Year Limited Warranty



SPECIFICATIONS

Model	55501201
Part	EM-EL-RC
Description	Emergency Light W/Remote Capability (2-head)
Input Voltage (VAC)	120/277
Wattage	2.4
Dimmability	NA
Average Rated Life ¹	50,000 hours
Typical Lumens ²	249
CCT ³	6500K
Location Rating	UL Damp
CRI ⁴	NA
Beam Angle	NA
Operating Temperature	Min 32°F (0° C), Max 104°F (40° C)
Power Factor	NA
R9	NA
DUV	NA
CBCP	NA
Operating Frequency (Hz)	50/60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





Emergency Light W/Remote Capability (2-head)

249lms | 120/277VAC | Model 55501201 | Part EM-EL-RC

SHIPPING INFORMATION

Model	55501201
Part	EM-EL-RC
UPC	849489009698
Product Dimensions (L x W x H in.)	13.74 x 4.13 x 3.50
Product Dimensions (L x W x H cm.)	34.9 x 10.5 x 8.9
Product Weight (lbs.)	1.48
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	6
Master Carton Bar Code	50849489009693
Master Carton Dimensions (L x W x H in.)	14.57 x 8.27 x 14.96
Master Carton Dimensions (L x W x H cm.)	37.0 x 21.0 x 38.0
Master Carton Weight (lbs)	11.46
Pallet Quantity	288

COMPATIBILITY

Dimmers: NA

Sensors: NA

AVAILABLE ACCESSORIES

Model	Part	Description	Wattage	Input Voltage	Case Pack
55503101	EM-ELR-H1	Emergency Light Fixture -Single (Wet Rated)	1.2W	N/A	12
55503201	EM-ELR-H2	Emergency Light Fixture -Double (Wet Rated)	2.4W	N/A	12

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256