



4FT High Output Linkable Strip Light

45 Watts 5000lms Strip Light LED 54573161

SPECIFICATIONS



The ETi 4' Linkable LED Strip Light offers exceptional performance as a high quality replacement for traditional fluorescent light sources. Lasting more than 5 times longer and maintenance costs. A special benefit of these ETi strip lights is the linking feature - multiple fixtures can be connected using a linking cable or end-to-end connector, both included. Engineered to be installed as either suspend and surface mounting, an optional mounting plate (Item 54657102) is also available. The strip lights are 120-277v, UL listed for use in damp locations, and suitable for installations from -4° F 95° F. Warranty 5 years.

Designed to be used anywhere a traditional fluorescent fixture is used. Typically used in work shops, garages and utility rooms. Other common applications in commercial, office, retail, restaurants, schools, hospitals and hotel/motel locations.

KEY FEATURES & BENEFITS

Installation as suspend and surface mounting
5000 Lumens & 45 Watts
Linkable via cable or end-to end -connector
120-277 Volt, 5000K, 80 CRI
cULus listed for Damp Locations
Rated life: 50,000 hours (45.6 years)

FIXTURE DIMENSIONS



SKU# 54573161
Dimension A= 48"
Dimension B= 2.28"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etissl.us/fcc15b

www.etissl.com
855-384-7754



4FT High Output Linkable Strip Light

45 Watts 5000lms Strip Light LED 54573161

SPECIFICATION DATA

Item Number	Description	Watts	Input Voltage [VAC]	Average Rated Life ¹	Typical Lumens ²	CCT ³	CRI ⁴	Power Factor	R9	DUV	CBCP	Beam Angle	Operating Frequency
54573161	4FT LED STRIP LIGHTR	45	120-277	50,000hours	5000	5000	80	/	/	/	/	/	50/60Hz
¹ Hours lifetime with 70% lumen maintenance													
² Thermally stable typical lumens													
³ in compliance with ANSI C77.378 201X													
⁴ Color rendering index/Ra													

SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions [L x W x H]	Item Weight [lbs]	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions [H x L x W]	Inner Pack Weight [lbs] Dimensions [H x L x W]	Master Pack QTY	Master Carton Bar Code	Master Dimensions [L x W x H]	Master Pack Weight [lbs]
54573161	849489 002804	48.03"x 1.81" x 2.28"	/	/	/	/	/	6	5084948 9002809	/	/



The Americas Headquarters
720 Corporate Woods Parkway
Vernon Hills, IL 60061
855-384-7754
www.etissl.com

