



- > Energy Saving 56 Watt Integrated LED
- > Cool White 4000K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty

4' High Lumen Output Vapor Tight

7000 lm | 120-277VAC | Model 64501141 | Part VT-4-70-840-MV-D



SPECIFICATIONS

Model	64501141
Part	VT-4-70-840-MV-D
Description	4' High Lumen Output Vapor Tight
Input Voltage (VAC)	120-277
Wattage	56
Dimmability	0-10v Dimming
Average Rated Life ¹	50,000 hours
Typical Lumens ²	7000
CCT ³	4000K
Location Rating	UL Wet (IP65 Rated)
CRI ⁴	≥80
Beam Angle	110°
Operating Temperature	Min -4°F (-20° C) Max 113°F (45° C)
Power Factor	>0.9
R9	16
DUV	0.0009
CBCP	2076
Operating Frequency (Hz)	50/60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





4' High Lumen Output Vapor Tight

7000 lms | 120-277VAC | Model 64501141 | Part VT-4-70-840-MV-D

SHIPPING INFORMATION

Model	64501141
Part	VT-4-70-840-MV-D
UPC	849489002309
Product Dimensions (L x W x H in.)	3' 11 13/64" x 4 29/32" x 3 19/32"
Product Dimensions (L x W x H cm.)	120 x 12.6 x 9.1
Product Weight (lbs.)	4.85
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489002304
Master Carton Dimensions (L x W x H in.)	4' 15/64" x 10 53/64" x 8 17/64"
Master Carton Dimensions (L x W x H cm.)	122.5 x 27.5 x 21.0
Master Carton Weight (lbs)	26.86
Pallet Quantity	80

COMPATIBILITY

Sensors: 90600144

Dimmer Brand	Dimmer Model#
Lutron	DVSTV
Lutron	MS-Z101
Lutron	IP710-LFZ

AVAILABLE ACCESSORIES

Model	Part	Description	Wattage	Input Voltage	Case Pack
90600144	NA	Step Dimming Motion Sensor	NA	120-277	4

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256