



40" Color Preference® Wrap Light

2600 lms | 120VAC | Ordering 56507113 | Part WR-40-26-802-SV-D

- > Energy Saving 30 Watt Integrated LED
- > Uses 50% Less Energy than Equivalent 60 Watt T8/T12 Fluorescent
- > Soft White 3000k CCT
Cool White 4000k CCT
Daylight 5000k CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free - No Bulb Replacements
- > 5 Year Limited Warranty



SPECIFICATIONS

Ordering	56507113
Part	WR-40-26-802-SV-D
Certification	56507113
Description	40" Color Preference® Wrap Light
Input Voltage (VAC)	120
Wattage	30
Dimmability	Triac
Average Rated Life ¹	50,000 hours
Typical Lumens ²	2600
CCT ³	3000/4000/5000k
Location Rating	UL Damp
CRI ⁴	80
Beam Angle Operating	110°
Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	13
DUV	-0.0016
Operating Frequency (Hz)	50/60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





40" Color Preference® Wrap Light

2600 lms | 120VAC | Ordering 56507113 | Part WR-40-26-802-SV-D

SHIPPING INFORMATION

Ordering	56507113
Part	WR-40-26-802-SV-D
UPC	849489006925
Product Dimensions (L x W x H in.)	40 x 4 x 2
Product Dimensions (L x W x H cm.)	122 x 15 1/4 x 7 1/2
Product Weight (lbs.)	2.78
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	2
Master Carton Bar Code	50849489006920
Master Carton Dimensions (L x W x H in.)	42.8 x 7.2 x 5.9
Master Carton Dimensions (L x W x H cm.)	109 x 18.2 x 15
Master Carton Weight (lbs)	8.12
Pallet Quantity	224

COMPATIBILITY

Dimmer Brand	Dimmer Model#
Lutron	DVCL-153PR-WH
Lutron	TGCL-153PH-WH
Lutron	TGCL-153PH-WH
Lutron	MACL-153MH-WH
Leviton	P-PKG1W-WH-R
Leviton	R62-06674-P0W
Eaton	R50-IPL06-10M
	AAL06-C1

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256