DATE:	PROJECT:
TYPE:	NOTES:
CATALOG #:	

FM | 7" LOW PROFILE FLUSHMOUNT

KEY FEATURES

Loq-prfile flushmount with integrated LED illumination and fixed bright-white color temperature. No replacement bulbs require.

CCT & Light Quality
- Fixed 4000K bright white; 80 CRI

Light Output & Efficacy
- 810 lumen; reported efficacy 70.43 lm/W
- 11.5W total input

Dimming, Voltage
- Non-dimmable | 120V,60Hz

SPECIFICATIONS

Construction
- 7-inch low profile flushmount; 1.78-inch overall height
- Integrated LED light source

Optics
- 120° beam angle
- Replacement diffuser lens avaliable separately

Electrical / Options
- 50,000 hour LEDs at L70 for reduced maintenance
- Power factor >0.9
- Operating Temperature: -4°F ~ 95°F (-20°C ~ 35°C)

Warranty

5-Year Standard Warranty. See terms at: ETISSL.com/warranty/



Damp Location

5 YEAR WARRANTY

KEY DATA	
LUMEN	810 LM
WATTAGE	11.5W
EFFICACY (LPW)	70.43 LM/W
REPORTED LIFE (HOURS)	L70 / > 50,000

Certifications & Test Data
- UL listed for damp location
- Driver rated for FCC part 15 Class B for use in residential or commercial appications

CATALOG LOGIC

FM	–	7	–	11	–	840	–	SV	–	N	–	O
Series		Size		Watts		CRI/CCT		Voltage		Dimming		ID
FM 7" Flushmount		**7** 7-inch		**11** 11.5W		**840** 80 CRI / 4000K		**SV** 120Vac		**N** Non-dimmabe		**O**

STOCK ORDERING INFORMATION

CATALOG PART NUMBER	ORDER NUMBER	DESCRIPTION	VOLTAGE	DIMMING	CRI	CCT	WATTS	LUMEN PACKAGE (NOMINAL)	EFFICACY
FM-7-11-840-SV-N-O	54663142	7" Low Profile FLushmount	120	Non-Dim	80	4000K	11.5	810	70.43

ETI Lighting
4873 Thurmon Tanner Parkway,
Flowery Branch, GA 30542

855.384.7754 | www.etissl.com
Quotes: quotes@etissl.com
Orders: etiorders@etissl.com

All specifications are subject to change without notice.
All reported values are typical values, measured under laboratory conditions @ 25° C (77° F).
Actual performance can vary slightly as a result of end-user application & environment.