

Vapor Tight

EZ Install Vapor Tight Fixtures 34w, 51w, & 56w



EZTM VAPOR TIGHTS

INSTALL

ETI[®] ADVANTAGE



- ✓ Durable stainless-steel latches
- ✓ Captive hinged lens makes for quick and EZ Installation
- ✓ Suspended or ceiling mount installation, Brackets included!
- ✓ Replaceable light engines and drivers
- ✓ NSF Rated

LIGHTING CONTROL AND SAFETY



90600144
Step Dimming Motion Sensor,
Microwave with Daylight Sensor



90600145
ON/OFF Motion Sensor, Microwave
with Daylight Sensor



90600143
Universal wattage BBU


AVAILABLE MODELS

Features & Specifications

- Wide 120° beam angle • 120-277V • >80CRI • 0-10V dimmable (51w and 56w) • Temp rating -22°F - 113°F
- L70 >50,000 • 5 Year limited warranty

Vapor Tight Selection Guide	STANDARD LUMEN 34W* 3600 LM 4000K	MID LUMEN 51W 5400 LM 4000K	HIGH LUMEN 56W 7000 LM 4000K
Base Model	54656241 VT-4-34-840-MV	54465141, VT-4-54-840-MV-D 54465161, VT-4-54-850-MV-D (5000K)	64501141, VT-4-70-840-MV-D 64501161, VT-4-70-850-MV-D
Base + Microwave Sensor	54656241-I VT-4-34-840-MV-OS	54465141-I VT-4-54-840-MV-D-OS	N/A
Base + BBU	54656341 VT-4-40-840-MV-EM, 40W with BBU	N/A	N/A
Base + Sensor & BBU	54656341-I VT-4-40-840-MV-EM-OS, 40W with BBU & Motion Sensor	N/A	N/A

PART NUMBER GUIDE



PRODUCT/SKU DETAILS

GENERAL SPECIFICATIONS:

Voltage	120-277VAC	Frequency	50/60 Hz.	CRI	80
Power Factor	>.90	THD	< 20%	Rating	cULus Wet
Temperature	-22°F to +113°F	Rated Life	50,000 hrs.	Warranty	5 Year Limited

ORDERING GUIDE

Part #	Model #	Description	Replaces	LED Watts	Lumens	LPW	CCT	Product Dimensions	CRI	Input Voltage	Case Pack
VT-4-34-840-MV	54656241	4' 34w Vapor Tight (NSF)	3 x 32w T8	34w	3600	106	4000K	48.0 x 4.6 x 3.0 in.	80	120-277V	2
VT-4-34-840-MV-OS	54656241-I	4' 34w Vapor Tight with Motion Sensor (NSF)	3 x 32w T8	34w	3600	106	4000K	48.0 x 4.6 x 3.0 in.	80	120-277V	2
VT-4-40-840-MV-EM	54656341	4' 40w Vapor Tight with Battery Back-Up (NSF)	3 x 32w T8	40w	3600	90	4000K	48.0 x 4.6 x 3.0 in.	80	120-277V	2
VT-4-40-840-MV-EM-OS	54656341-I	4' 40w Vapor Tight with Battery Back-Up and Motion Sensor (NSF)	3 x 32w T8	40w	3600	90	4000K	48.0 x 4.6 x 3.0 in.	80	120-277V	2
VT-4-54-840-MV-D	54465141	4' 51w Vapor Tight - 0-10V Dimmable (NSF)	3 x 32w T8	51w	5400	106	4000K	48.0 x 4.6 x 3.0 in.	80	120-277V	2
VT-4-54-840-MV-D-OS	54465141-I	4' 51w Vapor Tight with Motion Sensor - 0-10V Dimmable (NSF)	3 x 32w T8	51w	5400	106	4000K	48.0 x 4.6 x 3.0 in.	80	120-277V	2
VT-4-54-850-MV-D	54465161	4' 51w Vapor Tight - 0-10V Dimmable (NSF)	3 x 32w T8	51w	5400	106	5000K	48.0 x 4.6 x 3.0 in.	80	120-277V	2
VT-4-70-840-MV-D	64501141	4' 56w High Lumen Output Vapor Tight - 0-10V Dimmable	4 x 32w T8	56w	7000	125	4000K	47.2 x 4.9 x 3.6 in.	80	120-277V	4
VT-4-70-850-MV-D	64501161	4' 56w High Lumen Output Vapor Tight - 0-10V Dimmable	4 x 32w T8	56w	7000	125	5000K	47.2 x 4.9 x 3.6 in.	80	120-277V	4

Accessories

MC601V	90600144	Step Dimming Motion Sensor, Microwave with Daylight Sensor, Internally Mounted, Up to 49' mounting height, detection angle 150° (wall), 360° (ceiling), Compatible with 54465141, 54465161, 64501141, 64501161	N/A	N/A	N/A	N/A	N/A	4.0 x 2.1 in.	N/A	120-277V	4
MC603S	90600145	Motion Sensor, Microwave with Daylight Sensor, Internally mounted, Up to 19' mounting height, detection angle 150° (wall), 360° (ceiling) - Compatible with 54656241, 54656341, 54465141, 64501141, 64501161	N/A	N/A	N/A	N/A	N/A	3.5 x 1.4 in.	N/A	120-277V	4
EMJ-0825	90600143	Battery Back-Up for High Bays, LiFEPO4 Battery, illumination time ≥ 90 minutes @ 25w, recharge time 48 hours max - Compatible with 54656341	N/A	25w Max Output	N/A	N/A	N/A	2.2 x 10.1 x 9.9 in.	N/A	120-277V	6
N/A	95457326101	Aircraft Cable for Suspension Mounting for Flat Panels, High Bays, Strip Lights and Vapor Tights (Two 10' pieces)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	1

PACKAGING SPECIFICATIONS

Part #	Model #	UPC	UCC	Inner Carton Dimensions	Inner Carton Weight	Shipper/Master Carton Dimensions	Shipper/Master Carton Weight
VT-4-34-840-MV	54656241	849489009599	50849489009594	50 x 4.8 x 3.4 in.	5.3 lbs.	51 x 6.9 x 5.3 in.	13.6 lbs.
VT-4-34-840-MV-OS	54656241-I	849489005089	50849489005084	50 x 4.8 x 3.4 in.	5.5 lbs.	51 x 6.9 x 5.3 in.	14.0 lbs.
VT-4-40-840-MV-EM	54656341	849489009926	50849489009921	50 x 4.8 x 3.4 in.	7.0 lbs.	51 x 6.9 x 5.3 in.	14.9 lbs.
VT-4-40-840-MV-EM-OS	54656341-I	849489001791	50849489001796	50 x 4.8 x 3.4 in.	7.2 lbs.	51 x 6.9 x 5.3 in.	14.9 lbs.
VT-4-54-840-MV-D	54465141	849489009919	50849489009914	50 x 4.8 x 3.4 in.	5.3 lbs.	51 x 7.7 x 5.7 in.	12.8 lbs.
VT-4-54-840-MV-D-OS	54465141-I	849489001951	50849489001956	50 x 4.8 x 3.4 in.	5.5 lbs.	51 x 6.9 x 5.4 in.	15.3 lbs.
VT-4-54-850-MV-D	54465161	849489002293	50849489002298	50 x 4.8 x 3.4 in.	5.3 lbs.	51 x 6.9 x 5.3 in.	12.8 lbs.
VT-4-70-840-MV-D	64501141	849489002309	50849489002304	47.6 x 5.2 x 3.9 in.	6.5 lbs.	48.3 x 10.9 x 8.3 in.	26.9 lbs.
VT-4-70-850-MV-D	64501161	849489002316	50849489002311	47.6 x 5.2 x 3.9 in.	6.5 lbs.	48.3 x 10.9 x 8.3 in.	26.9 lbs.
Accessories							
MC601V	90600144	849489009742	50849489009747	6.4 x 6.4 x 6.4 in.	1.1 lbs.	21.1 x 12.8 x 5.6 in.	18.7 lbs.
MC603S	90600145	849489009759	50849489009754	6.1 x 3.8 x 2.2 in.	0.9 lbs.	19.1 x 12 x 4.5 in.	14.6 lbs.
EMJ-0825	90600143	849489009322	50849489009327	6.9 x 3.9 x 2.2 in.	3.5 lbs.	16.5 x 8.1 x 6.2 in.	20.5 lbs.
N/A	95457326101	849489009605	N/A	N/A	N/A	13.6 x 11 x 9.4 in.	15.4 lbs.