

DATE:	PROJECT:
TYPE:	NOTES:
CATALOG #:	

2' LOW PROFILE WRAP LIGHT

WITH PULL CHAIN | 2104 lm | 105 LPW | 4000K

KEY FEATURES

ETI's 2ft. LED Wraparound Light with Pull Chain is a great replacement for outdated fluorescent light fixtures.

- Modern linear shaped ceiling light with white durable PC diffuser/lens
- 50,000-hour life
- 20" On/Off pull chain

SPECIFICATIONS

Construction

- Low Profile Wrap—metal housing with decorative plastic end caps
- Pull Chain

Light Quality

- 4000K, 80+ CRI

Optics

- PC diffuser lens for zero pixelation and overall visual comfort
- Uniform, even light distribution

Installation and Function

- Easy installation with 2 Church key holes
distance between two keyholes is 23.2 inches
- Flushmount screws and drywall anchors included

Electrical

- 50,000 hour LEDs at L70 for reduced maintenance
- Operates at 120V, 60Hz
- Operating temperature: -4°F ~ 113°F
- Dimmable—TRIAC

* Always consult dimmer manufacturer for proper use, installation and compatibility (some dimmers may require a neutral in the wall box).

Warranty

5-Year Standard Warranty. See terms at: [ETISSL.com/warranty/](https://www.etissl.com/warranty/)



KEY DATA	
Lumen	2104
Wattage	20.07
Efficacy (LPW)	105
Reported Life (Hours)	L70 / 50,000

Certifications & Test Data

- All luminaires are built to UL 1598 standards and have the appropriate UL labels and information on product
- Damp location rated
- ENERGY STAR® rated (See Page 2 for search info.)
- IC Rated for direct contact with insulation
- Driver rated for FCC part 15 Class B for use in residential or commercial applications



2' Low Profile Wrap Light WITH PULL CHAIN | 2104 lm | 105 LPW | 4000K

CATALOG LOGIC

WRPC	2FT	2000LM	8	40K	SV
Series	Size	Lumens	CRI	CCT	Voltage
WRPC 2' Wrap with Pull Chain	2FT (2' Dia)	(Lumen Package) 2000LM	8 80CRI (min.)	40K 4000K	SV Single-Volt 120V

Notes:
1. This product is not configurable, Only designated 'Stock' SKUs are available.

STOCK ORDERING INFORMATION

Catalog Part Number	Order Number	Case QTY	Lumen Package	Delivered Lumens ¹	Wattage (Nominal)	Efficacy	CCT	CRI	Voltage	Dim	ENERGY STAR®
WRPC-2FT-2000LM-8-40K-SV	568051420	4	2000	2104	20	105	4000K	80 (min)	120V	TRIAC	Yes Search: 568051###

Notes: 1. For more delivered lumens and test data see below, or visit ETISSL.com

DIMENSIONS / DETAILS

Unit Weight
1.04 lbs.

PERFORMANCE / DATA

Lumen Maintenance

Ambient Temp.	TM-21 Lumen Maintenance (54,000 hours)
25° C (77° F)	89%
Ambient Temp.	TM-21 Theoretical L70 (hours)
25° C (77° F)	50,000

Load Information


Power Factor	.90
THD	< 20%
Frequency	60 Hz
Low Temp Start / Max Temp	-20° C (-4° F) / 45° C (113° F)

PHOTOMETRIC SAMPLE

Luminaire Data:

CCT & CRI	4000K, 80+ CRI
Delivered Lumens	2104
Wattage	20.07W
Efficacy	105
Beam Angle	50%=116° 10%=172°
Spacing	0° = 1.22 90° = 1.28

Candela Plot



Candela Distribution

Angle	0°	90°
0	721	721
5	717	717
10	704	708
15	685	694
20	660	673
25	627	646
30	589	615
35	546	579
40	500	539
45	452	496
50	399	447
55	346	396
60	288	344
65	230	289
70	173	235
75	116	181
80	64	130
85	22	80
90	3	34

% Effective Ceiling Cavity Reflectance

Ceiling	80%				70%				50%				30%				10%				0%
Wall	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Zonal cavity method—Effective floor reflectance = 20%																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99			
1	108	103	98	94	105	101	96	93	96	93	90	92	89	87	88	86	84	82			
2	98	89	82	76	95	87	81	75	84	78	73	80	76	72	77	73	70	68			
3	89	78	70	63	87	77	69	63	74	67	61	71	65	60	68	63	59	57			
4	82	69	60	53	79	68	59	53	65	58	52	63	57	51	61	55	51	48			
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	54	49	44	42			
6	69	56	47	40	67	55	46	40	53	45	39	51	44	39	49	43	39	36			
7	64	50	42	35	62	50	41	35	48	40	35	46	40	35	45	39	34	32			
8	60	46	37	31	58	45	37	31	44	36	31	43	36	31	41	35	31	29			
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26			
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23			

Photometric values based on tests performed in compliance with LM-63 & LM-79

Zonal Lumen Summary

