

DATE:	PROJECT:
TYPE:	NOTES:
CATALOG #:	

4' X 15" LOW PROFILE FLUSHMOUNT

3 CCT COLOR PREFERENCE® | NIGHTLIGHTR™

KEY FEATURES

- Low profile design with decorative beveled trim
- 50,000-hour life with L70 at 50,000
- TRIAC Dimming
- Adjust night light (Amber 2000K) with wall switch or dimmer
- 3 Field adjustable CCT (3000K/4000K/5000K)

SPECIFICATIONS

Construction

- Thin panel with decorative beveled white trim

Optics

- PC diffuser lens for zero pixelation and overall visual comfort
- Uniform, even light distribution

Installation

- Surface mount kit included:
 - 6 Mounting Screws
 - 3 Wire Connectors
 - 6 Drywall Anchors
 - 2 Safety Cables
 - 4 Pins
 - Location Paper and Lever

Electrical

- 60,000 hour LEDs at L70 for reduced maintenance
- Operates at 120V, 60Hz
- Operating temperature: -4°F ~ 113°F
- Triac dimming, down to 10%*
- ETi SSL's patented 3 CCT COLOR PREFERENCE® allowing for easy field-adjustable lighting output with switch located on product back


* Always consult dimmer manufacturer for proper use, installation and compatibility (some dimmers may require a neutral in the wall box).

Warranty

5-Year Standard Warranty. See terms at: ETISSL.com/warranty/



Regular Light Mode > Night Light Mode



KEY DATA	
Lumen Range	561 – 2203
Wattage Range	45 – 46
Night Light Wattage	20
Efficacy Range (LPW)	90 – 95
Reported Life (Hours)	L70 / 60,000



Certifications & Test Data

- All luminaires are built to UL standards, damp locations rated (See Page 2 for search info.)
- Driver rated for FCC part 15 Class B for use in residential or commercial applications
- RoHS Compliant



All specifications are subject to change without notice.

4' x 15" Low Profile Flush Mount ³ CCT COLOR PREFERENCE® | NIGHTLIGHTR™

CATALOG LOGIC

CLLP-NL	-	4000LM	-	8	-	CP3	-	SV	-	TD	-	W
Series		Lumens		CRI		CCT		Voltage		Dimming		Trim
CLLP-NL Low Profile Flushmount with NightlightR™		4000LM		8 80CRI (min.)		CP3 3 CCT Color Preference® 3/4/5000K		SV Single-Volt 120V		TD TRIAC Dimming		W White

Notes:


1. This product is not configurable, only designated 'Stock' SKUs are available.
2. Factory set at 3000K. Installing contractor responsible for ensuring desired CCT is selected during installation.

STOCK ORDERING INFORMATION ¹ (typical 2-3 day shipment lead time)

Catalog Part Number	Order Number	Product Description	Wattage (Nominal)	Nightlight Wattage	Lumen Package	Delivered Lumens ²	Efficacy (LPW)	CCT	CRI	Volt.	Dim
CLLP-NL-4000LM-8-CP3-SV-TD-W	56702114	4ft x 15in Flush Mount with Night Light Frosted Lens / White Trim	50	20	4000	4147	90	3000K	80+	120V	TRIAC
						4313	95	4000K			
						4299	93	5000K			

Notes: 1. Stock SKUs typically ship in 24-48 hours upon receipt of an approved released order 2. For more delivered lumens and test data see on page 3, or visit ETiSSL.com

DIMENSIONS / DETAILS



Unit Weight
13 lbs



Factory settings:
3000K

INSTALLATION KIT



PERFORMANCE / DATA

Lumen Maintenance

Ambient Temp.	TM-21 Lumen Maintenance (54,000 hours)
25° C (77° F)	90%
Ambient Temp.	TM-21 Theoretical L70 (hours)
25° C (77° F)	60,000

Load Information


Power Factor	.90
THD	< 20%
Frequency	60 Hz
Low Temp Start / Max Temp	-20° C (-4° F) / 45° C (113° F)

PHOTOMETRIC SAMPLE

Luminaire Data: @4000K

CCT & CRI	4000K, 80+ CRI
Delivered Lumens	4313
Wattage	45.2W
Efficacy	95
Beam Angle	50%=113° 10%=165°
Spacing	0° = 1.36 90° = 1.26

Candela Plot



Photometric values based on tests performed in compliance with LM-63 & LM-79

