



PRODUCT OVERVIEW

ETi SSL's Slim Canopy luminaire has a **small footprint** and offers sufficient light coverage, helping provide a safe, well-lit environment. The **3 selectable wattages and CCTs**, IP65, wet location rating, and bronze or white finishes make this canopy a practical and versatile outdoor lighting solution.


Equipped with 0-10V dimming, universal 120-277 voltage, this canopy is ideal for parking garages, drive throughs, walk ways and more.



INNOVATE. ILLUMINATE. INSPIRE.

SLIM CANOPY 3 LUMEN BOOST® | 3 CCT COLOR PREFERENCE®

PERFORMANCE SUMMARY

Lumen Packages	Lumen Pkg. Range (LB3)	Selectable Watt. Levels	CCT (CP3)	Distribution
Lumen Pkg 1	3800 – 7600	25 40 60	3000K 4000K 5000K	

Slim,
4.17" Profile



ELECTRICAL DATA

Operation: 120-277V, 50/60Hz

Low Temp Start / Max Temp: -30° C (-22° F) / 45° C (113° F)

Controls: 0-10V

CERTIFICATIONS & OTHER INFO


Warranty: 5 year

IK10 Impact Resistant

UL/cUL Listed: Wet, IP65 Rated



Easy Access for
Wattage Selection



Easy Access for
CCT Selection



MTO OPTIONS

Slim Canopies are also available with installed Occupancy Sensors.



ETI Lighting
720 Northgate Parkway, Wheeling, IL 60090 | TEL: 1.855.384.7754
E-mail: ETIorders@ETISSL.com | ETISSL.com

All specifications are subject to change without notice.

Slim Canopy