



PRODUCT OVERVIEW

ETI's bronze outdoor integrated LED wall pack with glass lens combines energy efficiency, **high performance**, and rugged construction with a **familiar, traditional look** to deliver enhanced performance.


It features three selectable CCTs and four selectable wattages for flexibility and efficiency. Equipped with 0-10V dimming, universal 120-277 voltage, and covered Photocell with enable/disable capabilities, the traditional wall pack is ideal for building-mounted doorways, pathway illumination, retail centers, industrial parks, schools/universities, multifamily facilities, and more.



INNOVATE. ILLUMINATE. INSPIRE.

TRADITIONAL LED WALL PACK 3 LUMEN BOOST® | 3 CCT COLOR PREFERENCE®

PERFORMANCE SUMMARY

Lumen Packages	Lumen Pkg. Range (LB3)	Selectable Watt. Levels	CCT (CP3)	Distribution
Lumen Pkg 1	4794 – 8500	30 40 50 60	3000K 4000K 5000K	 TYPE IV
Lumen Pkg 2	10514 – 14036	70 80 90 100	3000K 4000K 5000K	

Dusk to Dawn
Photocell w/
enable/disable
capability

Hinged Access
for wiring,
Wattage & CCT
select access



ELECTRICAL DATA

Operation: 120-277V, 50/60Hz

Low Temp Start / Max Temp: -40° C (-40° F) / 50° C (122° F)

Controls: 0-10V, Photocell Dusk-to-Dawn

CERTIFICATIONS & OTHER INFO

Warranty: 5 year

UL/cUL Listed: Wet location, IP65 Rated



Photocell cover



Conduit entry



Hinged wiring, wattage select,
and CCT select access

Removable heatsink allows for easier mount and install.

