

DATE:	PROJECT:
TYPE:	NOTES:
CATALOG #:	

DL 5" LOWPRO CANLESS DIRECT 4 CCT COLOR PREFERENCE® J-BOX MOUNT RECESSED DOWNLIGHT

KEY FEATURES

- Luminaire shall use ETI's patented Color Preference with 4 Selectable CCTs (2700K, 3000K, 4000K, 5000K), using Samsung LEDs
- 90+ CRI (JA8 Title 24 Compliant) | 50+ R9, high R13 value
- IC Rated for maximum thermal management
- Triac dimming down to 10%—quiet and flickering free
- Damp location

SPECIFICATIONS

Construction

- Durable die-cast aluminum low profile trim with 1/10" surface profile?
- Suitable for IC or Non-IC applications
- Matte white finish

Optics

- High impact, polymer diffuser lens for zero pixelation and overall visual comfort
- Uniform, even light distribution

Installation

- Two low-profile spring retention clips for a secure fit—no need for a separate recessed housing or junction box
- Easy to installed and service from below the mounting/ceiling surface
- Minimum 2" plenum space required to install the remote driver box
- Field select one of four CCTs at installation with an integral switch accessible on back side of luminaire. Factory set to 2700K.

Electrical

- >54,000 hour LEDs at L70 for reduced maintenance
- Operates at 120V, 60Hz
- ETI's patented 4 CCT COLOR PREFERENCE® allows for easy field-adjustable color temperature selection with switch located on back of luminaire
- Triac dimming, down to 10%*

* Always consult dimmer manufacturer for proper use, installation and compatibility (some dimmers may require a neutral in the wall box).

Warranty

5-Year Standard Warranty. See terms at: [ETISSL.com/warranty/](https://www.etissl.com/warranty/)



KEY DATA	
Lumens Range	964 – 1258
Wattage Range	13.16 – 13.35
Efficacy (LPW) Range	73 – 95
Reported Life (Hours)	L70 / >54,000
Input Current (mA)	126

Certifications & Test Data

- Built to UL 1598 standards and have the appropriate UL labels and information on product
- Damp location
- Adheres to LM63, LM79, LM80 and TM21 industry standards for photometric, lumen maintenance and lifetime calculations
- ENERGY STAR® rated (See Page 2 for search info.)
- Product can be used to comply with California Title 24 Efficiency Standards
- JA8 Title 24 Compliant
- IC Rated for direct contact with insulation
- Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements

